

Edge 1025



Product Snapshot

Proxim's Edge 1025 is the most versatile small wireless broadband solution available.

One device, multiple uses; whether you need a Point to Point endpoint, Multipoint CPE, or MultiPoint Base Station¹, the Edge 1025 fits the bill.

- Wide Band 5 GHz Radio
- 4x4 MIMO radio delivering up to 380 Mbps²
- Advanced QoS for quad-play applications
- AES 128 encryption and Radius authentication
- Full tilt and swivel mounting kit included.

Powered by WORP®

Proxim WORP enables the most efficient wireless broadband access possible in a packet-based network. Advanced QoS controls, committed interface rates, latency controls, IGMP snooping, and native multicast support allow granular service level management and the best video performance available in this product class.

Advanced Interference Management

Proxim ClearConnect™ combines multiple dynamic technologies and delivers the best interference management solution available.

Flexible Antenna Options

Includes an integrated 15 dBi 35-degree dual-polarity antenna and offers external connectors for extended range and MIMO 4x4 configuration options.

Smartphone Configurator

Proxim's BlueConnect mobile app enables fast and efficient setup, monitoring, and troubleshooting.

Rugged Reliability

IP67 rated metal enclosure to ensure years of reliable service in harsh environments, including high winds, high salt, and temperature extremes.

1. Full MultiPoint BaseStation Functionality requires the MP-1025-BS3-32SU-UPG upgrade license.

2. 4x4 MIMO requires an external antenna and can be configured as 4x4:2 for redundancy or 4x4:4 for higher throughput or smaller channel.

Specifications

PRODUCT MODELS

MP-1025-BS3-WD	Edge Multipoint 1025, Base Station, integrated antenna and RP-SMA	PN: 901-00367
MP-1025-BS3-32SU-UPG	Edge Multipoint 1025, Base Station, support for 1 to 32 SU license upgrade	PN: 997-00058

INTERFACES

WIRED ETHERNET	One auto MDI-X RJ45 10/100/1000Mbps Ethernet with PoE in
WIRELESS PROTOCOL	WORP® (Wireless Outdoor Router Protocol)

RADIO & TX SPECS

MIMO	2x2:2, 4x4:2 and 4x4:4
MODULATION	OFDM BPSK-QAM256
FREQUENCY	5.150 – 5.925 GHz (Subject to Country Regulations)
CHANNEL SIZE	20 and 40 MHz (license upgrade to 80 MHz)
TX POWER	Up to 24 dBm (dual chain) or 27 dBm (quad chain)
TX POWER CONTROL	0 - 21 dB, in 1 dB steps. Automatic TPC with configurable EIRP limit

	20 MHz	40 MHz	REQUIRES LICENSE UPGRADE 80 MHz
TX POWER	MCS0:	MCS0:	MCS0:
2 RF	24	23	21
4 RF	27	26	24
	MCS8:	MCS9:	MCS9:
2 RF	19	18	17
4 RF	22	21	20
RX SENSITIVITY (Per=10 ⁻⁶)	MCS0:	MCS0:	MCS0:
	-89	-86	-84
	MCS8:	MCS9:	MCS9:
	-67	-62	-59
Throughput-MIMO 2x2 Mode	122 Mbps	294 Mbps	380 Mbps
Throughput-MIMO 4x4 Mode (Requires External Antenna)	240 Mbps	380 Mbps	380 Mbps
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature		
	Automatic Transmit Power Control (ATPC) with EIRP limit support		

MANAGEMENT

REMOTE	Telnet and SSH, Web GUI and SSL/TLS1.2, TFTP, SNMPv3
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB
OTHER	Syslog, sFlow™ agent, SNTP and local time, Spectrum analyzer
Multi-Language Support	Web Interface available in English, French, Spanish and Chinese

SECURITY


ENCRYPTION	AES 128
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)

ANTENNA


Integrated 2x2 MIMO 15 dBi Dual Polarized 35 degree Panel Antenna plus Four RP-SMA Connectors
(Software switch between integrated antenna and connectors)

ANTENNA PATTERNS (Sector Mode)


H-pol Azimuth




V-pol Azimuth



H-pol Elevation



V-pol Elevation



QoS

Asymmetric Bandwidth Control Asymmetric UL/DL committed and maximum information rate per service flow

Packet Classification Capabilities 802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType

Scheduling Best Effort, Real Time Polling Services

NETWORK

MODES Bridging, Routing (RIP v2 and IP tunneling)

IP STACK IPv4 and IPv6 simultaneously

GATEWAY FEATURES DHCP Server & relay, NAT with Std ALGs, PPPoE end point with Proxy DNS

VLAN 802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging

POWER

802.3af/at compliant (MIMO 4x4 mode requires 802.3at)

POWER CONSUMPTION

10 W typical, 12 W max in MIMO 2x2 mode

22 W typical, 25 W max in MIMO 4x4 mode

ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - IP RATING	WIND LOADING
	-30° to 55° Celsius (-22° to 131° Fahrenheit) Temporary increases up to 60°C (140° Fahrenheit) will not impact operation of the unit.	-50° to 70° Celsius (-58° to 158° Fahrenheit)	100% relative humidity – IP67	180 km/h (112.5 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS NPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
MP-1025-BS3	310 x 226 x 98 mm (12.2 x 8.9 x 3.85 in)	170 x 217 x 56 mm (6.7 x 8.55 x 2.2 in)	2.85 kg (6.28 lbs)	1.24 kg (2.73 lbs)

SAFETY STANDARDS

IEC 62368-1:2014 & 60950-22:2016

CAN/CSA C22.2 No 62368-1:14 & No 60950-22:17

EN 62368-1:2014 + A11:2017 & 60950-22:2017

CERTIFICATIONS

CANADA

RSS-247 issue 2, RSS-102 issue 5, ICES-003 issue 7

EUROPE

RED EN 301 489-1 + EN 301 489-17 + EN 301 489-19 + EN 300 328 + EN 301 893 + EN 302 502 + EN 303 413

PACKAGE CONTENTS

- One Edge MP-1025-BS3 with integrated antenna plus four RP-SMA connectors
- Five SMA weather proofing caps
- One M25 weather proofing cable gland
- One power injector and country specific power cord
- One full axis mounting kit
- One Grounding kit
- One Quick Installation Guide

MTBF & WARRANTY

>250 000 hours, 2-year warranty, ServPak Extended Support available.

ABOUT PROXIM WIRELESS :

Proxim Wireless is a global leader in advanced wireless broadband and WiFi solutions that deliver high performance and high availability communications.

Celebrating 40 years of pioneering wireless solutions, Proxim is recognized for unparalleled reliability, superior performance, and drive for innovation.

© 2022 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo is a trademark of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.