



RISBO RW5000 Model

Point-to-Point/ Multi Point Radio - Data Sheet



RW5000



Product Description

RW5000 is a carrier-class radio that the RW5000 Series and supports 5.7 to 5.85 GHz frequency range.

The Radio complies with a factory default of 5.8 GHz Universal.

RW5000 delivers up to 2500 Mbps throughput.

The radio is connectorized for external antenna (2 x N-type) or integrated 26dBi antenna

Product Highlights

- 500-2500 Mbps Ethernet net throughput
- Long range - Up to 40 km / 25 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site synchronization to maximize capacity
- Configurable asymmetric throughput
- Advanced OFDM & MIMO technologies for operation in nLOS/NLOS and dense radio environments
- Point-to-Point & Point-to-Multipoint on a single platform
- Flexible capacity, software upgradeable
- Support SyncE and V1588v2

Product Specifications:

Configuration					
Architecture	Outdoor Unit connectorized antenna (2 x N-type) or integrated antenna				
PoE to ODU Interface	Outdoor CAT-6; Maximum cable length: 100m for 10/100BaseT and 75m for 1000BaseT/2500Base-T, POE				
Radio					
Max Capacity	2500 Mbps net aggregate throughput				
Range	Point to Point UP to 120 km / 75 miles, Point to Multipoint up to 40km/25miles				
Channel Bandwidth	Configurable: 10, 20, 40, 80 MHz (for the default band), 160 MHz				
Modulation	MIMO-OFDM (BPSK/QPSK/16QAM/64QAM/256QAM/256QAM, 1024QAM)				
Adaptive Modulation, Coding & Channel BW	Supported				
Automatic Channel Selection	Supported upon power up				
DFS	Not Supported				
Diversity	Supported				
Spectrum Viewer	Supported				
1588 v2 TC	Supported				
Max Tx Power	25 dBm				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6				
Encryption	AES 128				
Support Indoor units	RISBO PoE devices (9921W101X)				
Uplink / Downlink Allocation	Configurable: Symmetric or Asymmetric				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
TDD Intra Site Synchronization	Supported				
TDD Inter Site Synchronization	Supported through common GPS receiver per site				
Option 82	Supported				
RADIUS Authorization	Supported				
RADIUS User authentication	Supported				
Syslog	Supported				
Supported Bands					
Band	CBW 10MHz [GHz]	CBW 20MHz [GHz]	CBW 40MHz [GHz]	CBW 80MHz [GHz]	Radio Compliance
5.8 GHz FCC/IC	5.730-5.845	5.730-5.845	5.730-5.845	5.730-5.845	FCC 47CFR Part 15.407; ISED RSS-247
5.8 GHz MII	5.725-5.850	5.725-5.850	5.725-5.850	5.725-5.850	CMIIT RTA
Mechanical					
ODU Dimensions	19(w) x 19.5(h) x 4(d) cm Not included Antenna, 37(w) x 37(h) x 8(d) cm Antenna included.				
ODU Weight	<2kg , <2.5kg				
Power					
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	< 13W				
Environmental					
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion in water up to 1m)				
Safety					
US/CAN (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
CE/IEC	EN/IEC 60950-1, EN/IEC 60950-22				
EMC					
FCC	47 CFR, Part15, Subpart B, Class B				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
CAN/CSA-CEI/IEC	CISPR 22-2010 Class B				

Warranty: 3 years

Ordering Info

Model: RW5000

Part Number: RW5000 ODU

Description: RW5000 ODU, supporting multi frequency bands at 5.x GHz, factory default 5.8 GHz Universal.

HS Code: 85.17.62.

Made in Singapore



RISBO is Trademark in Singapore / Malaysia

Datasheet information can be changed by manufacturer without prior notice

RISBO TECHNOLOGIES SDN BHD (1496123-H)

Suite A1 36F, Menara Maxis, KLCC, 50088, Kuala Lumpur Malaysia

Tel: +603 2615 0028 <https://www.risbo.com.my>

RISBO TECHNOLOGIES (SINGAPORE)PTE LTD (UEN:201432280R)

133 New Bridge #15-07 Chinatown Point 059413 Singapore.

Tel: +65 9882 6588 <https://www.risbo.com.sg>